


LED VEG LIGHT


520W

electrivo 



Precise Control

0-10V dimming control for individual fixture or fixture group dimming control(daisy chain via RJ11 cable)



SNAP ON/OFF!

Patented Design

Application

(Suitable for mother room , propagation , vegetative growth.)

- Indoor Farming
- Vertical Farming

Features & Benefits

- Constant current driver, durable life
- Full-spectrum, similar to sunlight, higher crop yield
- IP65 waterproof rating, suitable for high humidity application
- 0-10V dimming
- Flicker free
- Suspension and ceiling mounting option, mounting height 6" - 48"
- Application environment: indoor cultivation

- **One-click snap-on assembly, easy to install and upgrade.**
- **Dimmable upto 100 fixtures via daisy chain.**
- Sustainable packaging to minimize packaging and transportation cost.
- Adjustable hanging cable, adaptable to different stage of the grow cycle.
- Robust mechanical and electrical connection for product reliability.
- Independent external driver,easy installation and upgrade.
- Separable modular design, customizable to unique cultivation requirement.
- Modular design to maximize selling configuration while minimizing redundant inventory.

LED VEG LIGHT

520W PPE2.6 μ mol/J


Features & Benefits

Input Power	520W
Photosynthetic photon flux	1350 μ mol/s
Luminous Efficacy	2.6 μ mol/J
Viewing Angle	110°
CRI	>88
Input Voltage	100-277Vac 50/60Hz
Amp Draw	4.73A@120V, 2.67A@220V, 2.46A@240V, 2.15A@277V
PF	>0.9
THD	<20%
Driver Surge protection	6KV
Dimming	0-10V
LED Type	3000K+5000K 450nm+660nm(Samsung/Seoul Diodes)
Housing	Aluminum Alloy
Housing Color	Silver
Heat Output	1847 BTU
Operating Temperature	-10~40°C
Operating Humidity	10%-90% RH
Storage Temperature	-25~60°C
Storage Humidity	10%-90% RH
Warranty Time	5years
N.W (KG)	11.5Kg/25.35LBS
G.W (KG)	13.5Kg/29.76LBS
Packing Dimension(mm)	1162*245*245mm

Performance Data

Model	Input Voltage	Input Power	PPF	PPE	ETL	DLC	FCC
GL6-M10-520-B66-A1D	100-277Vac	520W	1350 μ mol/s	2.6 μ mol/J	Yes	Yes	Yes

Dimension Drawing




Length (L)	1045mm (41.1")
Width (W)	1042mm (41.0")
Height (H)	140mm (5.5")

Recommended Application


Multi-layer	4-5FT wide benches, 4-6 in from canopy
Room	6x6FT Vegetative
Tent	6x6FT Vegetative

electrivo


Spectral Distribution



PPFD Reading -- 4FT to 4FT area




1.2m 48"



0.45m 18"

0.6m 24"



0.3m 12"